

CERTIFICATE OF CONFORMITY OF THE FACTORY PRODUCTION CONTROL

Certificate No.:
2388-CPR-23-04176 Rev. 1.0

Initial certification date:
19-04-2023

Validity end date:
19-04-2026

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product(s)

Structural products of Aluminium and aluminium alloys for construction works
to be use in metal structures or in composite metal and concrete structures

placed on the market under the name or trade mark of

Hydro Extrusion Drunen B.V.

Alcoalaan 1, 5151 RW Drunen, The Netherlands
and produced in the manufacturing plant(s)

Hydro Extrusion Drunen B.V.

Alcoalaan 1, 5151 RW Drunen, The Netherlands

Hydro Extrusion Harderwijk

Industrieweg 15, 3846 BB Harderwijk, The Netherlands

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 15088:2005

under system 2+ are applied and that

**THE FACTORY PRODUCTION CONTROL IS ASSESSED TO BE IN CONFORMITY WITH
THE APPLICABLE REQUIREMENTS**

This certificate will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.

For more details see Appendix accompanying this Certificate.

Place and date:
Barendrecht, 2023-05-21

For the issuing office:
Notified Body 2388, The Netherlands

Check Validity



Bjørn Spongsveen
Management Representative

Appendix to Certificate

Certificate history:

Revision	Description	Issue Date
0.0	Initial Certificate	2023-04-21
1.0	Correction of the manufacturings plant name	2023-05-15

Additional information to the scope of certificate

Product Standard	EN 753-3:2019+A1:2022
Product(s)	Extruded Profiles
Dimension Standard	EN 755-9:2016 / EN 12020-2:2022

Wrought Aluminium Alloys AW-6000 series

Grade	Temper Condition	Width/Section/Mould size (mm)		Thickness (mm)		Length (mm) / Weight (Kg)
		min	max	min	max	max
EN AW-6005(A) EN AW-AISiMg(A)	T6	15	420	1,0	25	-
EN AW-6060 EN AW-AIMgSi	T6 T66	15	420	1,0	25	-
EN AW-6063 EN AW-AIMg0.7Si	T6 T66	15	420	1,0	25	-
EN AW-6082 EN AW-AISi1MgMn	T6	15	420	1,0	25	-

Declaration of performance and marking of product

When meeting with the terms and conditions, as required, the manufacture shall draw up an EC declaration of product performance and legally affix the CE mark followed by the notified factory production control certification body identification number of DNV (2388).

End of Certificate